

DATASHEET DS-DSP-17



GRP TACTILE PLATES

MATERIAL CHARACTERISTICS



Quality Assurance

Manufactured in accordance with our ISO 9001 accredited Quality Management System, the structural integrity of the specified material is high grade. A suggested life span of 25 years is expected, but not guaranteed, and is based on a number of variables: environmental, installation process, maintenance, loading and traffic conditions.



Chemical Resistance

GRP is resistant to a wide range of chemicals, across a wide temperature spectrum. GRP can be made using different resin systems to achieve specific chemical resistant properties. Please refer to our seperate chemical resistance chart SOS-DST-10.



ٌ Slip Resistance

The integral angular quartz gritted surface has been Tested in accordance with BS7976-2 and provides an exceptional level of slip resistance. Lifespan depends on frequency of use.



Fire Resistance

All products contain a fire resistant additive and comply with Euro Class 1 and ISO11952-2. Performance is equivalent to ASTM E84 class 1 and BS476 part 7class2 flame spread to give a 30 minute burn time.



🗭 uV Stable

All panels are manufactured with a high quality UV inhibitor to prevent UV degradation.



Self-Coloured

All Quartzgrip® tactile flooring is pigmented throughout during manufacture, and does not require any secondary treatment such as powder coating or paint spraying. Standard colour is Beige (RAL1003).



KG Light Weight and Durable

Weighing around 1/3 of the alternative solutions, Quartzgrip® moulded fibreglass is relatively lightweight in comparison, and can be manually manoeuvred into place without the requirement for mechanical assistance.

Quartzgrip® tactile floor is exceptionally durable, with an ability to withstand impact, reducing the risk of permanent bucking and deformation. Floor panels measure 400 x 400mm. They are easy to install, surface mounting with minimal downtime or groundwork required. Panels are hardwearing and weather resistant. They are: ideal for internal as well as external applications, and DDA and Building Regulations Compliant.

FOR MORE INFO Email: info@decksafe.se















3



DATASHEET DS-DSP-17



GRP TACTILE PLATES

Related Products



Stair Treads



GRP Handrail



Stair Nosing



Flat Plate

FOR MORE INFO Email: info@decksafe.se

Visit: www.decksafe.se















